discreet

comfortable

reliable

New

phonito Intra

The smallest ITE Inductive Receiver

AUTOMATIC SQUELCH CIRCUIT
NOISE AND LOUDNESS FILTER
BATTERY END OF LIFE WARNING
COMPATIBLE WITH ALL INDUCTIVE SYSTEMS

PHONAK
communication systems

The new phonito Intra

Technical Specifications
Max. Audio Output@3kHz Vol. 115 dB SPL Adj. Up from 100 dB
Frequency range 300 Hz bis 5 kHz
Distortion Less than 2%
Amplifier, Full custom IC, Battery end of life, Squelch, AGC
AGC (Auto. Gain Control)
Attack time 10 msec
Release time 1.8 sec
Receiver magnetic
Battery life with Phonak approved type Approx. 100 hrs.
Weight, incl. Battery 1.3 grams
CE Conformity EMC + ESD

Is the inductive receiver with an optimum anatomic design. It fits completely in the canal of either left or right ear and incorporates special functions:

- **new anatomic shape**
- **new** battery compartment
- loudness limiting
- audio squelch
- battery end-of-life warning
- **new** wax quard system (lateral openings prevent from blocking with ear wax)
- **new black pouch,** small and discreet.

Light weight, easy to use, phonito Intra, built on the successful phonito standard, offers you the performances of the latest technologies. **phonito Intra:** when high technology corresponds to the standard.

We have the solution!

Our core area of competence is the development and manufacture of ultra miniaturized communication devices. Consequently, the products are state of the art, always pushing the boundaries of possibility. With them, users can communicate easily and discretely with one another.

PHONAK

communication systems

Phonak Communications AG, Länggasse 17, CH-3280 Murten, Schweiz
Telefon +41 (0) 26 672 96 72, Fax +41 (0) 26 672 96 77
www.phonakcom.ch, info@phonakcom.ch