

BlueTalk



Part-No.: 0131000-69 + 0910010



BlueTalk Adapter

The BlueTalk Adapter forms the interface between a Bluetooth-enabled mobile phone or radio and an industry-headset. Depending on your needs different headsets can be connected. Speak of the user is only transferred when pressing the push-to-talk button. This way the transmission of noise is reduced to a minimum.

In addition to the integrated push-to-talk button of the BlueTalk, a wireless push-to-talk button is available. An optional 2-key-option of the wireless push-to-talk buttons also offers various special functions, such as full-duplex operation. Their digital ID enables the parallel operation of several systems in the immediate vicinity. The BlueTalk Adapter is distinguished by the following features:

- Connection with Bluetooth-enabled mobile phones from V. 2.0 (Incl. Apple iPhone)
- Connection with analogue/digital radios on request
- Long battery life through integrated lithium-polymer battery
- Voice announcements give status and warning messages
- Call receiving/termination and redial
- Wireless send button with 1 button (only PTT) or with 2 buttons (PTT and full duplex)
- Robust housing with dirt- and water-repellent membrane keyboard
- Cloth clip for mounting ex. on a belt

Technical data:

BlueTalk

Material:	ABS-plastic
Operation voltage:	3,7 V (LiPo-battery)
Battery life:	ca. 8h (depending of usage)
Send frequency:	2,4 Ghz (ISM-Band)
Range of use:	max. 5 m
Bluetooth standard:	Bluetooth Ver. 2.0
Headset connection:	12pin Hirose-plug (HR10A-10P-12S)
Temperature range:	-20°C to 55°C
Dimensions (LxWxH):	70mm x 44mm x 18mm
Weight:	93 g

Wireless Send button

Material:	ABS-plastic
Operation voltage:	3 V DC (coin cell CR-2032)
Battery life:	ca. 12 months
Send frequency:	868 Mhz (ISM-Band)
Range of use:	max. 5 m
Dimensions (LxWxH):	57mm x 35mm x 9mm
Temperature range:	-20°C to 55°C
Weight:	16 g

TECHNICAL DATA